

EZ CARE FLOOR COATING REMOVER

GROUNDBREAKING CLEANER TECHNOLOGY COMPATIBLE WITH AN AUTO SCRUBBER. The EZ CARE Floor Coating Remover is designed to remove up to four coats of EZ Care Floor Coating in one pass by using an auto scrubber.

- Liquifies EZ Care Floor Coating for fast removal of up to four coats in one pass.
- Eliminates conventional manual stripping
- Increases productivity by reducing the time and labor needed for a full removal and recoat.
- Streamlines the floor care workflow, reduces crew size, and simplifies training vs. conventional stripping.

DOES NOT CONTAIN INTENTIONALLY ADDED PFAS*



EZ Care Floor Coating Remover is part of the **EZ CARE** Floor Care system and is specifically designed to be used along with **SC Johnson Professional® EZ CARE** Floor Coating, **EZ CARE** Heavy Duty Scrub Pads and **EZ CARE** High Speed Conditioning and Polish Pad.

COMPATIBLE WITH AN AUTO SCRUBBER

SKU	DESCRIPTION	CASE PACK	IN USE GALLONS/LITRES PER BOTTLE
362837	EZ Care Floor Coating Remover	6x32oz /946mL	1:64 Dilution Up to 16 Gal. / 60.56 L per bottle

*PFAS are perfluoroalkyl and polyfluoroalkyl substances, which are a class of fluorinated organic chemicals containing at least one fully fluorinated carbon atom.

Use Instructions:

Removes up to 4 coats of SC Johnson Professional® EZ CARE Floor Coating in one pass.

USE COLD WATER FOR ALL APPLICATIONS. DUST MOP AREA PRIOR TO CLEANING TO REMOVE CONTAMINANTS.

PLACE PROPER BLOCKADES

Floors will be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.

PREPARE the EZ Care Floor Coating Remover according to label instructions and add to bucket or auto scrubber.

TO REMOVE: Apply liberal amounts of remover solution to floor. If using automatic scrubber machine apply while scrubbing. Let dwell for 15 minutes. Ensure remover solution does not dry re-wet as necessary.

For best results, perform two passes. On first pass, scrub with swing machine or auto scrubber without picking up remover solution. On second pass, mop or auto scrub floor while picking up remover solution. **Repeat application if necessary.**

Rinse floor with clean water. Allow floor to completely dry before applying SC Johnson Professional® EZ Care Floor Coating.

TO CLEAN:

May be used as an alkaline cleaner on uncoated concrete, quarry tile, unglazed ceramic, natural stone, rubber, brick, and slate. Refer to label instructions for dilution and clean as usual with a string mop or auto scrubber.

SAFETY PRACTICES TO FOLLOW

It's good business practice to assure that your employees have read and understood the product labels and Safety Data Sheet before using this product. The label use directions and SDS contain important hazard warnings, precautionary statements and first aid procedures. This information is available on-line at www.scjp.com or by calling 1-800-248-7190 in the US and 1-888-362-7267 in Canada.

DO NOT USE UNDILUTED. Best to apply in a well-ventilated area. Do not apply on surfaces with temperatures below 50°F (10°C). Not intended for outdoor spaces. Not intended for use on wood. Test, in an inconspicuous area, for adhesion on concrete, polished concrete and highly polished marble and granite.

INGREDIENTS:

2-(2-Aminoethoxy)ethanol (929-06-6); Isopropanolamine (78-96-6); Dimethyl 9-Decenamide (1356964-77-6); PEG-7/PPG-2 Propylheptyl Ether (166736-08-9); Whole Cut Fatty Acid (67701-05-7); Water (7732-18-5); Fragrance (Proprietary), Dye (Proprietary).
Made without phosphates

PRODUCT SPECIFICATION

Color	Orange; Clear at dilution
pH	13.53
pH at dilution	11.3
Density	8.25 g/cm ³
Fragrance	Fresh
Shelf-Life	3 Years
Substrate compatibility	VCT, LVT, Vinyl Asphalt, Vinyl Asbestos, Sheet Vinyl, Rubber, Linoleum, Terrazzo, Honed Marble, Honed Granite, Natural Stone, Brick, Slate, Quarry Tile
Incompatible materials	Do not mix with bleach or any other household cleaners or strong bases.



EZ CARE FLOOR COATING REMOVER
Can be applied and removed with an auto scrubber

SAY GOODBYE TO CONVENTIONAL STRIPPING

Contact your SC Johnson Professional sales representative and discover the EZ way to achieve a durable, high-gloss finish and eliminate the conventional stripping process.

SC Johnson Professional USA, Inc.
Charlotte, NC 28217

SC Johnson Professional CA Inc.
Brantford, ON N3T 5R1

www.scjp.com

scJohnson
PROFESSIONAL
A family company®